

# BIM-FAQS/CALL™

## BIM-FAQS/CALL™ alerts personnel by activating an alphanumeric pager

**BIM-FAQS/CALL™ extends the automation capabilities of BIM-FAQS/PCS™ and BIM-FAQS/ASO™.**

It interfaces directly to an SNPP server that allows two-way pager capabilities using TCP/IP FOR VSE™ from CSI International.

**Use the BIM-FAQS/CALL™ Call Lists to designate up to five contacts with unique messages and replies.**

BIM-FAQS/CALL provides four types of Call List, allowing you to use different Call Lists during different times of day.

Set up the Call Lists as required for the time periods below:

### For message definitions

- DAY1—0800–1730
- NIT1—1730–0100
- HOM1—0100–0800
- WEN1—Weekend (Saturday and Sunday)

### For non-1S78I messages

- DAY2—Workday, such as Monday through Friday
- HOM2—Not a workday, such as Saturday and Sunday

### For commands triggered by AR and SMSG

- DAY3—0800–1730
- NIT3—1730–0100
- HOM3—0100–0800
- WEN3—Weekend (Saturday and Sunday)

### For other types of commands not already covered

- DAY4—0800–1730
- NIT4—1730–0100
- HOM4—0100–0800
- WEN4—Weekend (Saturday and Sunday)

### Use the BIM-FAQS/CALL™ Reply and Action fields to enter the replies and actions available for the contact to use.

Enter a maximum of five replies that describe the type of action taken if the reply is chosen.

If the contact does not require a reply, leave the Reply and Action fields blank. This displays a message informing the contact that no reply is required (for example, *WARNING No Reply Given or Message will Not be 2WAY*).